

Body Snatcher Crate Sportsman

All cars participating in the newly proposed class will be inspected under strict scrutiny to make sure all safety issues are adhered to...if you fail inspection, you will not be allowed to compete.

- 1) 5 Point approved safety harness with stamped manufactured date visible. (Hans Device Recommended)
- 2) Snell Approved Helmet
- 3) Approved Racing Fire-suit, Underwear, Gloves, Arm Restraints, and Shoes
- 4) All Teams required too have working Fire Extinguishers in Pit Area
- 5) Fuels Cells required and securely fastened and be covered with tinwork. Shutoff valve required in driver cockpit and clearly marked
- 6) Batteries must be secure and covered
- 7) Must have approved design driveshaft loop
- 8) Aluminum Racing seats only. (Fully Contained is recommended) Steel plate underneath seat required for safety purposes
- 9) Driver's compartment must be enclosed with tinwork
- 10) 602 Crate Motors only (No Exceptions) (Same motor as Spec Sportsman)
- 11) Two return springs required for throttle assembly in separate locations
- 12) Toe Strap required for Gas Pedal
- 13) Proper roll bar padding required around the driver's head area
- 14) All fuel and power lines must be securely fastened
- 15) Wheel base minimum is 102" and maximum is 108"
- 16) Single hoop front bumper only
- 17) Side rub rails required
- 18) Rear bumper can only be as wide as the frame rails and then tapered towards rear wheels
- 19) Motor must be fully covered with hood. Provisions for flared tin to protect headers is okay
- 20) 2x4 frame required under motor and driver areas
- 21) Full floor pan required and securely fastened
- 22) Roof is optional. If roof is used it can be no wider or longer than 3 inches past the outer edge of roll cage and should be tapered down
- 23) Motor plate required
- 23) All cars must be self-starting
- 24) Pump Gas only (Periodic Checking)
- 25) Approved Mufflers required and securely fastened
- 26) Transponder required
- 27) Quick Change or approved rears only. (NO live rears)(Open or Closed driveline)

- 28) Torsion bar or spring type suspension allowed
- 29) 4 Wheel brakes required
- 30) Oil Type racing shocks only. (NO Gas Shocks) (Track is seeking shock manufacturer to come up with an affordable shock package designed for reliability and cost)
- 31) Steel Wheels only (Bead locks approved)
- 32) Racing type transmissions allowed
- 33) Track will designate the right rear tire for competition (No Exceptions)(Designated air pressure on right rear tire will be chosen)
- 34) No offset drivelines
- 35) Driver must sit in center of frame of frame rails
- 36) Steering rod should have safety strap
- 37) Rock screen in front of driver required
- 38) Number lettering will be 18" high and placed on cockpit tin and on roof if roof is utilized
- 39) Drivers name must be 12" high placed on bottom of cockpit tin
- 40) No wings on car of any kind (Tail section tin must be pointing downward or squared off)
- 41) Nosepiece on race car is optional but cannot look or act as a wing